









Drywall Hanger







Broaden Worldwide Co., Ltd

Established in 2009, BROADEN WORLDWIDE Co., Ltd. currently engages in the capacity of an authorized sales agent for various leading Taiwanese steel and stainless steel mills diversified field of steel coils. polymers and other threaded hardware products. The latest addition to the family is our patent SpreadStop Anchor and SpreadStop Hanger; innovative self gripping drywall anchors which, given their one-step. hassle free design, will spread through the DIY market like a brushfire.

BROADEN WORLDWIDE Co., Ltd. look forward to hearing from you and to forming a long-term, mutually rewarding business relationship.















ANCHORS & FIXATIONS

SpreadStop Hanger

Self-gripping Drywall Hanger

Product Description

SpreadStop Hanger is the only true one-step self-gripping drywall hanger on the market. It eliminates the need for wall stud searching, measuring, marking or pilot-hole drilling; line up your work piece and drill away one-step, a few seconds, and you're done!

SpreadStop Hanger consists of three parts, a screw with hanger, a patented spread-stop nylon sheath, and a self-drilling tip.

The self-drilling tip first makes a pilot hole, and guides our patented spread-stop nylon sheath through and threads in until flush against the wall. Continue drilling and you will notice a change in torque, which comes from the nylon sheath forming a locknut type fastener, shrinking in length but at the same time expanding in diameter, gripping firmly onto the drywall.

Features & Benefits

- 1 / No pre-drilling required, a true One-Step installation
- 2 / Utilizes our Spread-Stop Technology, which forms a locknut type fastener and grips firmly onto your drywall.
- 3 / Patented design installs fast and easily in drywall.

Perfect for

Electrical boxes, picture hanging lighting fixture, shelving etc.

Products sizes & suitable drywall thickness

Size		Suitable Dry	wall Thickness	Clearance behind Drywall		
inch	mm	inch	mm	inch	mm	
1/4×2-7/16	M6.3x62	Drywall 1/2	Drywall 12mm	1-7/8	48mm	

Load Capacities

Material	Size (inch)	Tensile max (lbs)	Shear max (lbs)	Tensile max (kg)	Shear max (kg)	Hold up to max	
						lbs	kg
Drywall 1/2	1/4 x 2-5/16	100	82	45	37	75	33

- 1 / The maximum hanging load is intended as a guideline only and cannot be guaranteed.
- 2 / Maximum load may be less, based on quality / thickness of drywall and dimensions of object being hung.
- 3 / Not recommended for ceiling applications.
- 4 / Industry safety standards recommend using only 1/4 of the maximum values as the safe working load.

Product materials

Carbon Steel SAE1022 + Nylon

Tools required

Screw Driver: #2 Phillips

Installation instructions



1

Using a Phillips screwdriver or a Hand drill press SpreadStop Hanger slightly onto the drywall. Set hand drill at a low gear and clutch at 1/3 of the total Torque settings.



2

Apply pressure: turn SpreadStop Hanger until a pilot hole is made and the nylon sheath slips through. (DO NOT push with excessive force; let the self-drilling tip do its job)



3

Turn SpreadStop Hanger until flush against the wall and you feel a firm resistance.



1

Continue to turn until the SpreadStop Hanger starts spinning freely.



5

Hang Away!

For more details regarding installation and usage, please visit WWW.SPREADSTOP.COM.TW